



- 1. 11004** Torque Rod Bush suit 40,000 lbs rated application.
- 2. 11081** Complete Torque Rod Assembly suit 40,000 lbs application, comes fitted with **11004** replaceable Torque Rod bushes.
- 3. 83520** (Easy Mount) specially designed for horizontally mounted Torque Rod bushes. **13520** is the fixed OEM Bush suit 46,000 lbs rated application. **18551** Install/Removal tool to suit **83520** & **13520** bushes.
- 4. 11152** Complete Torque Rod Assembly suit 46,000 lbs rated application, comes fitted with replaceable bushes **13520**.
It's advised to upgrade **11081** 40,000 lbs rated Torque Rod to **11152** 46,000 lbs rated Torque Rod when possible by DTNA, refer 32-51 Freightliner Service Bulletin.

Note: More Torque Rod options available to make your own Torque Rod.

- 13683** Torque Rod End fitted with **13520** (Standard) Bush.
 - 13790** Torque Rod End fitted with **83520** (Easy Mount) Bush.
 - 13690** Torque Rod End fitted with **13520** (Standard) Bush, length is 33-7/16".
 - 13691** Torque Rod End fitted with **13520** (Standard) Bush, length is 25-7/16".
 - 13789** Torque Rod End fitted with **83520** (Easy Mount) Bush, length is 25-7/16".
- 5. 11005** (Standard Version) Spring Pin Bush can be installed either side of the Spring. **11083** (Anti-Walk) Spring Pin Bush has an added shoulder to stop the bush from walking out of the spring. **11161** Install/Removal tool with both **11005** & **11083** bushes.
 - 6. 1R12-603** suit all Airliner Suspension & ride heights.

