

Page 1 of 6 PRO1-011

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 10/23/23

Classification of the Hazardous Chemical (in accordance with WHS Regulation)	

1. PRODUCT & COMPANY IDENTIFICATION

	II I RODGOT & COMIT ANT IDENTIFICATION
Product Name:	ProOne® EP-2 GOLD INDUSTRIAL GRADE GREASE
Chemical Name:	Grease
Synonyms:	NA .
Trade Names:	ProOne® EP-2 GOLD INDUSTRIAL GRADE GREASE
Product Uses & Restrictions:	Lubricating Grease
Distributor's Name:	Garlock and STEMCO
Distributor's Address:	Unit 2, 198 Walters Rd, Arndell Park, NSW, 2199, Sydney, Australia
Emergency Phone:	Poisons Information Centre: Australia: 13 11 26 New Zealand: 0800 764 766
Business Phone / Fax:	Tel: 1800 427 5625
	Chemical Name: Synonyms: Trade Names: Product Uses & Restrictions: Distributor's Name: Distributor's Address: Emergency Phone:

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE DAMAGE. MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE.

Classification: Asp. Tox. 1; Skin. Irrit. 2; Eye Dam. 1; Aquatic Chronic 4

<u>Hazard Statements</u> (H): H304 – May be fatal if swallowed and enters airways. H315 – Causes skin irritation. H318 – Causes serious eye damage. H413 – May cause long lasting harmful effects to aquatic life.

Precautionary Statements (P): P264 – Wash thoroughly with soap and water after handling. P280 – Wear protective gloves/eye protection. P273 – Avoid release to the environment. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do NOT induce vomiting. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P321 – Specific treatment see this container label. P332+P313 – If skin irritation occurs: Get medical advice/attention. P362+P364 – Take off contaminated clothing and was it before reuse. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 – Immediately call a POISON CENTER/doctor. P405 – Store locked up. P501 – Dispose of contents/container to an approved waste disposal plant.



3. COMPOSITION & INGREDIENT INFORMATION

							9	EXP	SURE L	IMITS	N AIR (n	ng/m³)	25
					AC	GIH		NOHSC			OSHA		ſ
		ppm ppm ppm		1									
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY	64742-54-7	PY8035501	265-157-1	30-70	5	NF	NF	NF	NF	5	NF	NF	MIST
PARAFFINIC8	Asp. Tox. 1; H	1304											
CALCULA SUL FONATE	61789-86-4	NA	263-093-9	20-30	NA	NA	NF	NF	NF	NA	NA	NA	
CALCIUM SULFONATE	Skin Sens. 1;	Eye Irrit. 2; H31	7, H319										
CALCIUM	26264-06-2	NA	247-557-8	1.0-10	NA	NA	NF	NF	NF	NA	NA	NA	
DODECYLBENZENESULFONATE Skin Irrit. 2; Eye Dam. 1; Aquatic Chronic 4; H315, H318, H413													
THIODIETHYLENE BIS [3-(3,5-DI-	41484-35-9	NA	255-392-8	1.0-10	NA	NA	NF	NF	NF	NA	NA	NA	0
TERT-BUTYL-4-HYDROXY- PHENYL) PROPIONATE]													
ProOne® PROPRIETARY	NA	NA	NA	0.0-10	NA	NA	NF	NF	NF	NA	NA	NA	

* contains less than 3% Dimethyl Sulfoxide (DMSO)

4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	DO NOT INDUCE VOMITING. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
		Eyes:	If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.
		Skin:	Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned.
		Inhalation:	Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration.



Page 2 of 6 PRO1-011

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision Date: 10/23/23 Classification of the Hazardous Chemical (in accordance with WHS Regulation) 4. FIRST AID MEASURES - cont'd 4.2 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Ingestion: May cause transient mild-eye irritation with short-term contact with liquid, spray or mist. Eyes: This product can cause mild, transient skin irritation with short-term exposure. This product can cause Skin: allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. No significant adverse health effects are expected to occur upon short-term exposure to this product. Inhalation: Aspiration of liquid into the lungs can cause severe lung damage or death. 4.3 Symptoms of Overexposure: Eyes: Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas The product Skin: can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 4.4 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 4.5 Chronic Health Effects: Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects. 4.6 Target Organs: Eyes, Skin, Respiratory System. 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH 1 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 1 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: This material can burn but will not readily ignite. This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, phosphorus and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released. 52 Extinguishing Methods: Dry Chemical, Foam, Carbon Dioxide, Water Fog. 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations, Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Use normal hygiene practices. Avoid breathing vapors. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. 7.3 Special Precautions: Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning. Keep container tightly closed when not in use. Do not store at temperatures above 120°F (49°C) Store away from strong oxidizers.



Page 3 of 6 PRO1-011

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision: 1.0 SDS Revision Date: 10/23/23 Classification of the Hazardous Chemical (in accordance with WHS Regulation) 8. EXPOSURE CONTROLS & PERSONAL PROTECTION OTHER OSHA Exposure Limits: ACGIH NOHSC ppm (mg/m3) CHEMICAL NAME(S) TLV STEL ES-TWA ES-STEL ES-PEAK STEL IDLH PEL DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 5 NA 5 NF NF 5 NA NA MIST PARAFFINIC 8.2 Ventilation & Engineering Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used. 8.3 Respiratory Protection: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states. 8.4 Eye Protection: Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing or spraying is anticipated. Wear goggles and face shield if material is heated above 125 °F (51 °C). Have suitable eye wash water available. 8.5 Hand Protection: Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.6 **Body Protection:** Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g. neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. Remove oil contaminated clothing. Launder oil contaminated clothing before reusing. Contaminated leather goods should be removed promptly and discarded. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Blue colored semi-solid paste 9.2 Odor Mild petroleum odor 9.3 Odor Threshold: NA 9.4 NA 95 Melting Point/Freezing Point: NA Initial Boiling Point/Boiling 9.6 NA Range: 9.7 Flashpoint: 275 °C (527 °F) 9.8 Upper/Lower Flammability Limits: 9.9 Vapor Pressure: Negligible at ambient temperature 9.10 Vapor Density NA 9.11 Relative Density: 0.886 - 0.899.12 Solubility NA 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature NA 9.15 Decomposition Temperature: NA 9 16 Viscosity: NA Other Information: 9.17 VOC: < 1%

10. S	TABIL	YTI.	& F	REA	CTI	VITY
-------	-------	------	-----	-----	-----	------

10.1	Stability:	Stable at normal temperatures.
10.2	Hazardous Decomposition Products:	Fumes, smoke, carbon monoxide, silicon oxides.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, and close proximity to incompatible substances.
10.5	Incompatible Substances:	Strong oxidizing agents.
5.7 10		euong onaitang agoine.



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards

SAFETY DATA SHEET

Page 4 of 6 PRO1-011

SDS Revision Date: 10/23/23

Classification of the Hazardous Chemical (in accordance with WHS Regulation) 11. TOXICOLOGICAL INFORMATION 11.1 Routes of Entry: Inhalation: NO Absorption: YES Ingestion: YES This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is 11.2 Toxicity Data: available for some of the components of the product and is presented below: Distillates, Petroleum, Solvent-Refined, Heavy Paraffinic - LD₅₀ (oral, rat) > 5000 mg/kg; LD₅₀ (dermal, rabbit) > 2000 mg/kg. 11.3 Acute Toxicity: Oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. Chronic Toxicity: 11.4 In long term studies (up to two years) no carcinogenic effects have been reported in any animal species tested. This product contains a severely hydrotreated distillate with less than 3 % DMSO extract as measured by IP 346 and is, 11.5 Suspected Carcinogen: therefore, not considered a carcinogen. 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity This product is not reported to produce reproductive effects in humans. 11.7 Irritancy of Product: See section 4.3 118 Biological Exposure Indices: NE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: This product is believed to be stable. Engineering controls should be put in place to prevent release to the environment. 12.2 Effects on Plants & Animals: No evidence is currently available on this product's effects on plants or animals 12.3 Effects on Aquatic Life There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local hazardous waste laws Special Considerations 132 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 14 1 49 CFR (GND): NOT REGULATED 14.2 IATA (AIR): NOT REGULATED 14.3 IMDG (OCN): NOT REGULATED TDGR (Canadian GND): 14.4 NOT REGULATED 14.5 ADR/RID (EU): NOT REGULATED 146 SCT (MEXICO): NOT REGULATED 147 ADGR (AUS): NOT REGULATED 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. CERCLA Reportable Quantity 15.4 Calcium Dodecylbenzenesulfonate: 454 kg (1,000 lbs) 15.5 Other Federal Requirements None of the ingredients are listed as Hazardous Air Pollutants (HAPs). None of the ingredients are listed as Toxic Pollutants under the Clean Water Act (CWA). None of the ingredients are listed as Priority Pollutants under the Clean Water Act (CWA). This product does not contain any Class 1 or Class 2 ozone depletors. Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects)

Page 5 of 6 PRO1-011

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards SDS Revision Date: 10/23/23 Classification of the Hazardous Chemical (in accordance with WHS Regulation) REGULATORY INFORMATION – cont'd State Regulatory Information: Calcium Dodecylbenzenesulfonate is found on the following state criteria lists: Massachusetts Hazardous Substances List (MA) and Pennsylvania Right-to-Know List (PA). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). Other Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Toxic (T). Risk Phrases (R): 45 - May cause cancer. Safety Phrases (S):53-45 - Avoid exposure - obtain special instructions before use. In case of accident or if you feel unwell seek medical advice immediately (show the label where Calcium Dodecylbenzenesulfonate: Harmful (Xn). Risk Phrases (R): R36/37/38-65 - Irritating to eyes, respiratory system and skin. Harmful - may cause lung damage if swallowed. Safety Phrases (S): S (2)-23-24-62 - Keep out of the reach of children. Do not breathe fumes/mists/vapors/spray. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label where possible. 16. OTHER INFORMATION Other Information: 16.1 DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE DAMAGE. MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE. Wash thoroughly with soap and water after handling. Wear protective gloves/eye protection. Avoid release to the environment. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Specific treatments see this container label. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and was it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Store locked up. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN. Terms & Definitions: 16.2 See last page of this Safety Data Sheet. 16.3 Disclaimer This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & ProOne, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. Prepared for: ProOne, Inc. 16.4 1370 S Acacia Ave Fullerton, CA USA Tel: +1 (714) 327-0262 e-mail: info@pro-one.us http://www.pro1industrial.com

16.5

Prepared by:

ShipMate, Inc. P.O. Box 787

Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com

Sisters, Oregon 97759-0787 USA



Page 6 of 6 PRO1-011

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 1272/2008/EC & GHS Standards

SDS Revision Date: 10/23/23

Classification of the Hazardous Chemical (in accordance with WHS Regulation)

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

Chemical Abstract Service Number	
LIMITS IN AIR:	
American Conference on Governmental Industrial Hygienists	
Ceiling Limit	
Exposure Standard (Australia)	
Immediately Dangerous to Life and Health	
U.S. Occupational Safety and Health Administration	
Permissible Exposure Limit	
Short-Term Exposure Limit	
Threshold Limit Value	
Time Weighted Average	
	LIMITS IN AIR: American Conference on Governmental Industrial Hygienists Ceiling Limit Exposure Standard (Australia) Immediately Dangerous to Life and Health U.S. Occupational Safety and Health Administration Permissible Exposure Limit Short-Term Exposure Limit Threshold Limit Value

FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	



PERSONAL PROTECTION RATINGS:

Α		G	
В		Н	0000
С		1	
D	606	J	
E		K	0000
F		X	Consult your supervisor or SOPs fo special handling directions.























Dust & Vapor Half-Mask Respirator



or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	TY LIMITS IN AIR:
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
¥	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s				
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts				
TDio	Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom				
TD _{lo} , LD _{lo} , & LD _o or TC, TC _o , LC _{lo} , & LC _o	Lowest dose (or concentration) to cause lethal or toxic effects				
IARC	International Agency for Research on Cancer				
NTP	National Toxicology Program				
RTECS	Registry of Toxic Effects of Chemical Substances				
BCF	Bioconcentration Factor				
TLm	Median threshold limit				
log Kow or log Koc	Coefficient of Oil/Water Distribution				

PEGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	((a)	②	①	®		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

F	經	M	*	8	9	×	X
С	E	F	N	0	т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

\Diamond	③	③	\Diamond	\Diamond		\Diamond		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment