Color-Plast Shims

Color-Plast Sheets, Shims and Spacers

Color-Plast is a tough, plastic material that is completely impervious to oil grease, even in temperatures up to 121°C. It will not swell or distort after long use and will withstand high torque loads. Color-Plast has the same compressibility as a brass shim. Another feature of the color plast is it wrinkle- free structure, ensuring easy handling and installation.



Clear .001"(0.025mm)

Tan .0015"(0.038mm)



Blue Striped (Orange)* .002" (0.051mm)

Cream .003" (0.076mm)

Black Striped (clear)* .004" (0.102mm)

Clear Striped Silver (Silver)* .005" (0.127mm)

Khaki .0075" (0.191mm)

Dark Brown .010" (0.254)

Sheets are colour-coded according to thickness, making shim, spacers and sheet selection very fast and easy



Black with Lime Stripes (Lime)* .0125" (0.318mm)

Pink (Olive)* .15" (0.381mm)



.020" (0.508mm) Red Striped (Aqua)* .025" (0.635mm)

Black



White

.030" (0.762mm Purple Striped

0.040" (1.016mm)

Green Striped 0.050" (1.270mm)

Color-Plast can be supplied as:

- Sheets standard sheet size is 20" x 50" (508 x 270mm)
- Strips/Sheets -cut to supplied widths \geq
- Cut shims/spacers to supplied dimensions ۶
- \triangleright Shim Kits - to suit complete shim requirements of equipment

| Construction Material | Polyester | Tri-Acetate | Vinyl |
|---------------------------|---|---|---|
| Thickness | 0.028mm (0.001") Clear 0.038mm (0.0015") Pink 0.051mm (0.002") Blue Striped (Orange) * 0.076mm (0.003") Cream 0.10mm (0.004") Black Striped (clear)* 0.127mm (0.005") Silver Striped (Silver)* | 1.02mm (0.040") Striped Purple 1.27mm (0.050") Striped Green 1.52mm (0.060") Striped Orange | 0.191mm (0.0075") Khaki 0.254mm (0.010") Dark Brown 0.318mm (0.0125") Black w/ Lime Stripes (Lime)* 0.381mm (0.015") Red Striped (Olive)* 0.508mm (0.020") Black 0.635mm (0.025") Yellow Striped (Aqua)* 0.762mm (0.030") White |
| Distortion Temperature | 121°C | 93 °C | 74 °C |
| Applications | For applications against oil, petroleum, Aromatic and non-aromatic fuels. High compressibility useful when lightweight sheet metal flanges are involved. For use with gear case, crankcases and oil pans and containers | | |

Garlock