



EndiT DU Casing End Seal

For dirt- and moisture-protected sealing of annular space between carrier and casing pipe



AREA OF APPLICATION

Ending of pipe-in-pipe systems for new installations of house connections; requirement for a dirt- and moisture-protected sealing solution

MATERIAL

Material type: EPDM Rubber
Shore hardness: Shore A 50 ° ±5
Rubber thickness: 5 bis 6 mm

PROPERTIES

Kit article: fastening straps stainless steel

Color: black

Information: Solution for fixed standard combinations of carrier and casing pipes; ability to compensate eccentric installed carrier pipes; easy installation due to pre-molded end seal



Civil engineering



Water



Energy



PRODUCT INFORMATION

FEATURES

- Protection against moisture and dirt
- Also suitable for retrofitting
- Individual or special solutions possible

AREAS OF APPLICATION

Pipes carrying media (e.g. gas pipeline, water pipeline, sewage pipeline, etc.) below motorways, main roads, railway tracks, etc. are often laid in casing pipes, here they are used as protective pipe closures.

PRODUCT DESCRIPTION


The end seals are used to seal the annular space between the carrier pipe and the casing pipe against dirt and moisture.

NOTE

Casing end seals are available for new installations, and for retrofitting.



INSTALLATION



1

Pull small end of the seal over the carrier pipe.

2

After connections the pipe, pull the large end of the seal over the casing pipe as far as possible. The fitting position of DU seals is determined by their design.

3

Place stainless steel straps around the small and large diameters. Pull the free end of the strap at least 50 mm through the square opening in the clamp and then fold it. The folded end must be placed under the fastening strap. Tighten the clamp as far as possible using a socket spanner. See also the installation instruction for steel strap