



SealiT Manhole Connection Seal

Flexible connection of pipes to manhole systems



FIELDS OF APPLICATION

For the flexible connection of pipes to manhole systems and as connection pieces on pipework

MATERIAL

Material type: SBR-Rubber compliant with EN 681-1 WCL

PROPERTIES

Description: Good mechanical strength, high resistance to weathering and acids

SIZE

Pipe outside diameter ND 110, 160, 200



Building Construction



Civil Engineering



Water



HVAC



Industry



PRODUCT INFORMATION

PROPERTIES

Manhole connection

FIELDS OF APPLICATION

Manhole connection for plastic pipes

DESCRIPTION

No special tools are required for quick and easy installation; the seal is simply inserted into the annular space



CERTIFICATES

TEXT

- ZERTIFIKAT_ISO_9001_2015
- AEO-CERTIFICATE Authorized Economic Operator "AEOC (customs simplification)"



INSTALLATION



1

The hole has to be drilled according to the tolerance ± 2

2

Press seal in the hole without lubricant. Make sure that the seal is fully pushed in.


3

The end of the pipe should be lubricated. Push pipe into the seal. Make sure that pipe is pushed in at least 50 mm.



2

SealiT Manhole Connection Seals are used for flexible connection between pipes and manholes. Storage in a dry place at a temperature above 0°C.



3